


COIL AND LEAF SPRINGS TESTING STAND



BUILT TO LAST



www.ascorail.pl

Youtube - ASCO RAIL

ASCO RAIL sp. z o.o.

ul. Wielowiejska 53, 44-120 Pyskowice

POLAND

T: +48 32 230 45 70

F: +48 32 233 21 34

export@ascorail.pl www.ascorail.pl



COIL AND LEAF SPRINGS TESTING STAND



The correct state of resilient elements is a prerequisite for the proper functioning of rail vehicles. For this reason the coil and leaf springs must be regularly tested to determine their properties and characteristics. Offered by ASCO RAIL testing devices provide testing to the full extent required for coil and leaf springs.

THE STAND IS DESIGNED TO TESTING THE FOLLOWING TYPES OF SPRINGS:

- Coil springs and a set of those springs,
- Volute springs,
- Leaf springs and parabolic leaf springs,
- Metal-rubber springs (optional),
- Others resilient elements (optional).

THE STAND CONSIST OF:

- Test bench with hydraulic unit, measuring table and trolleys, guarding device, force and distance sensors,
- Electrical cabinet with a control panel and PLC controller,
- Laptop with a database and registration results.

BASIC TECHNICAL PARAMETERS OF THE STANDARD VERSION:

- Maximum load: 180 kN,
- Actuator stroke: 450 mm,
- Test load accuracy: < 1%,
- Deflection measurement accuracy: 0,1 mm,
- Maximum height in the free status of the tested spring: 500 mm,
- Maximum external diameter of the tested spring: 250 mm,
- Minimum internal diameter of the tested spring: 60 mm,
- Maximum length of the tested leaf spring: 1400 mm,
- Maximum height of the tested leaf spring: 300 mm,
- Supply voltage: 3 x 400 V,
- Dimensions: test bench 650 x 1970 x 2270 mm; control cabinet 600 x 960 x 520 mm,
- Special designs possible in accordance with individual customer requirements.



TEST RESULTS:

- Length of the spring in mm at a given load,
- Height of the leaf spring in mm at a given load,
- Axial stiffness w kN/mm,
- Characteristic diagram (kN-mm),
- Other results of the test on request (lateral stiffness, lateral displacement, bending strength, angle bend).

BASIC CHARACTERISTICS:

- Automatic testing possibility of resilient elements with different procedures (VPI, technical conditions and others),
- Easy to introduce new test elements and test parameters,
- The full test parameters recording (date, a person who tests, test elements etc.),
- Possibility of device status remote diagnostics and change test parameters.



ASCO RAIL sp. z o.o.
ul. Wielowiejska 53
44-120 Pyskowice
POLAND
T: +48 32 230 45 70
F: +48 32 233 21 34

export@ascorail.pl
www.ascorail.pl

BUILT TO LAST



www.ascorail.pl

PARTNER REPRESENTATIVE

